



- ① Metal Roof Deck
- ② EQUUS Debotack2.5T/F C175 or Colphene 3000 Vapour Barrier
- ③ EQUUS SOPRAROCK mineral wool thermal insulation
- ④ EQUUS DeboPlast or DeboFlex base sheet
- ⑤ EQUUS DeboPlast, DeboFlex or Debotack 2.5 T/F C175 base sheet, dressed to parapet as separate piece
- ⑥ EQUUS DuO High Tech 4 Slates/F C180 Firecare cap sheet
- ⑦ EQUUS cap sheet, dressed to Parapet as separate piece
- ⑧ EQUUS bitumen fillet or approved alternative
- ⑨ EQUUS Sopradere Quick or Aquadere bitumen primer
- ⑩ Approved capping (by others)



E-mail : admin@equus.co.nz
 Web : www.equus.co.nz

PROJECT :	Warm Roof on Metal Standard Detail - DuO		
TITLE :	Plywood parapet detail with roof cap flashing (Mineral insulation)		
NUMBER :	SDWRM-D2c	SCALE :	1 : 3
DRAWN BY :	NKT	DATE :	17-Jan-2022
		REVISED :	

EQUUS Waterproof Membrane Details are specially drawn for use by Local Authorities, Building Contractors, Equus Applicators, Architects and design professionals. All details are drawn to assist in the development of project specific details. Details may be modified where necessary to accommodate job specific requirements but must be approved by Equus Industries Ltd. All components must be supplied by Equus Industries Ltd. Equus reserves the right to alter or upgrade details at any time without prior notice.

