## **Chevaline Dexx**

# - Flexible Reinforced Roof and Deck Membrane eQUIS



**Dexx** is a liquid applied, glass fibre mat reinforced membrane for use in sealing old and new flat and near-flat roofs, walk-out decks and patios. The material is a heavy-bodied water-borne acrylic paste ready to use from the container. It is formulated for high adhesion, and water resistance, also toughness combined with flexibility in the cured film. This makes is particularly useful where areas are subject to foot traffic and light vehicular traffic.

Dexx is supplied as standard grey and white but custom colours are available to match any colour chart.

- Available in 4L and 15L pails
- Spreading rate of 2-2.5sqm/litre/coat

#### **Key Benefits:**

- 100% NZ made
- 35 years of proven performance in New Zealand conditions
- Excellent durability & UV resistance
- Easy to apply
- Applicable to a variety of surfaces in both horizontal and vertical situations
- Wide colour range available
- Easy long term maintenance

#### **Application (Minimum System):**

- Primer specific to substrate
- Dexx Bodycoat
- Glass fibre mat (laid into wet bodycoat)
- Dexx Bodycoat
- Dexx Bodycoat
- Wearcoat/Glazecoat as Topcoat



Glass fibre mat laid into wet bodycoat



Chevaline Dexx bodycoat



Completed project



Completed project

### - Chevaline Dexx applied to residential balconies













