

DUO System

- Two Layer Bitumen Roofing Membrane



The two layer **DUO** system consists of a 2.5mm basesheet, with a 4.3mm capsheet torched ovetop to form a total 6.8mm thick system designed by Belgium waterproofing company De Boer and is used all over the world. **DUO** roofing membrane provides a hard, stable, UV-resistant, but flexible modified bitumen product finished with pressed coloured slates for use in sealing old and new, flat and near-flat roofs. The system has been assessed within the New Zealand Building Code and can be used on substrates such as plywood and concrete.

- Available in colours GW (Grey White) WGG (White Green and Grey) and AGR (Black)
- Mechanically fixed solutions and no flame systems available
- Duotherm Warm Roof systems also available

Key Benefits:

- De Boer has over 90 years of proven performance around the world
- 6.8mm thick
- Proven UV resistance
- Approved/licensed installation
- Excellent durability and easy maintenance
- Life expectancy of at least 35 years in all climates
- Material warranties provided

Application:

- Substrate primed with De Boer Duo Primer
- Roll and Torch on Basesheet
- Roll and Torch on Capsheet
- Detailing
- Inspection and Sign off

BRANZ and Codemark Appraised

- BRANZ Appraisal No. 685
- Codemark 30060



Equus Southern

Unit 6/100 Fitzgerald Ave, Christchurch

Ph: 03 353 2434

E: southern@equus.co.nz

Equus Central

45 Hutt Rd, Petone, Wellington

Ph: 04 576 0333

E: central@equus.co.nz

Equus Northern

Unit E/1 Henry Rose Pl, Albany, Auckland

Ph: 09 415 4314

E: northern@equus.co.nz

www.equus.co.nz

- De Boer Duo applied to residential and commercial roofs



Equus Southern
Unit 6/100 Fitzgerald Ave, Christchurch
Ph: 03 353 2434
E: southern@equus.co.nz

Equus Central
45 Hutt Rd, Petone, Wellington
Ph: 04 576 0333
E: central@equus.co.nz

Equus Northern
Unit E/1 Henry Rose Pl, Albany, Auckland
Ph: 09 415 4314
E: northern@equus.co.nz

www.**equus**.co.nz