

ALSAN FLASHING QUADRO



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SDS 3170

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : ALSAN FLASHING QUADRO

SDS n°1122e

UFI : 61R0-2ANQ-N00F-GEW8 PXQ0-JAYA-A00Y-T3A6 U4R0-KAC3-X00X-4SGA E6R0-3A1H-800F-T42D

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Registered company name : SOPREMA .

Address : 14, Rue de Saint-Nazaire.67025.STRASBOURG.FRANCE.

Telephone : 03 88 79 84 00. Fax : 03 88 79 84 01.

sds@soprema.fr

www.soprema.com

NEW ZEALAND SUPPLIER:

EQUUS INDUSTRIES LTD Sheffield

Street, Riverlands Estate Blenheim,

Marlborough

Ph: +64 03 5780214

Fax: +64 03 578 0919

Email: admin@equus.co.nz

National Poison Centre: 0800 764 766

1.4. Emergency telephone number : +44 (0)1 235 239 670.

Association/Organisation : CARECHEM 24 .

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Acute inhalation toxicity, Category 4 (Acute Tox. 4, H332).

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Specific target organ toxicity (repeated exposure), Category 2 (STOT RE 2, H373).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07



GHS08

Signal Word :

WARNING

Product identifiers :

EC 215-535-7

XYLENE

EC 608-245-0

3-OXAZOLIDINEETHANOL, 2-(1-METHYLETHYL)

EC 224-518-3

MORPHOLINE-4-CARBALDEHYDE

EC 931-274-8

HEXAMETHYLENE DIISOCYANATE, OLIGOMERS

EC 223-861-6

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE

EC 685-296-5

PRÉPOLYMÈRE D'OXYDE DE PROPYLÈNE, D'OXYDE D'ÉTHYLÈNE ET DE DIISOCYANATE DE TOLUÈNE (PTMGE)

607-241-00-6

HEXAHYDRO-4-METHYLPHTHALIC ANHYDRIDE

EC 259-627-5

3-IODO-2-PROPYNYL BUTYLCARBAMATE

Additional labeling :

EUH204

Contains isocyanates. May produce an allergic reaction.

Hazard statements :

H226

Flammable liquid and vapour.

H315

Causes skin irritation.

ALSAN FLASHING QUADRO

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure .
H412	Harmful to aquatic life with long lasting effects.
Precautionary statements - Prevention :	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314	Get medical advice/attention if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
Precautionary statements - Disposal :	
P501	Dispose of contents / container in accordance with local / regional / national / international regulation.

2.3. Other hazards

The mixture contains substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

As from 24 August 2023 adequate training is required before industrial or professional use.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 1330-20-7 EC: 215-535-7 REACH: 01-2119488216-32-xxxx XYLENE	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373	C [1]	10 \leq x % < 25
CAS: 100-41-4 EC: 202-849-4 REACH: 01-2119488216-32-xxxx ETHYLBENZENE	GHS07, GHS08, GHS02 Dgr Flam. Liq. 2, H225 Asp. Tox. 1, H304 Acute Tox. 4, H332 STOT RE 2, H373 Aquatic Chronic 3, H412	[1]	2.5 \leq x % < 10
CAS: 28770-01-6 EC: 608-245-0 3-OXAZOLIDINEETHANOL, 2-(1-METHYLETHYL)	GHS07, GHS05 Dgr Acute Tox. 4, H302 Skin Sens. 1, H317 Eye Dam. 1, H318		2.5 \leq x % < 10
CAS: 1305-78-8 EC: 215-138-9 REACH: 01-2119475325-36-xxxx OXYDE DE CALCIUM	GHS07, GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335	[1]	1 \leq x % < 2.5
CAS: 4394-85-8 EC: 224-518-3 REACH: 01-2119987993-12 MORPHOLINE-4-CARBALDEHYDE	GHS07 Wng Skin Sens. 1, H317		0.1 \leq x % < 1

ALSAN FLASHING QUADRO

CAS: 28182-81-2 EC: 931-274-8 REACH: 01-2119485796-17-xxxx HEXAMETHYLENE DIISOCYANATE, OLIGOMERS	GHS07 Wng Skin Sens. 1, H317 Acute Tox. 4, H332 STOT SE 3, H335		0.1 <= x % < 1
CAS: 4098-71-9 EC: 223-861-6 REACH: 01-2119490408-31-xxxx 3-ISOCYANATOMETHYL-3,5,5-TRIMETHYL CYCLOHEXYL ISOCYANATE	GHS06, GHS09, GHS08 Dgr Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Acute Tox. 1, H330 Resp. Sens. 1, H334 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]	0.1 <= x % < 1
CAS: 68132-86-5 EC: 685-296-5 PRÉPOLYMÈRE D'OXYDE DE PROPYLÈNE, D'OXYDE D'ÉTHYLÈNE ET DE DIISOCYANATE DE TOLUÈNE (PTMGE)	GHS08 Dgr Skin Sens. 1, H317 Eye Irrit. 2, H319 Resp. Sens. 1, H334		0.1 <= x % < 1
INDEX: 607-241-00-6 CAS: 19438-60-9 EC: 243-072-0 HEXAHYDRO-4-METHYLPHTHALIC ANHYDRIDE	GHS08, GHS05 Dgr Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317	C [6]	0.1 <= x % < 1
CAS: 55406-53-6 EC: 259-627-5 3-IODO-2-PROPYNYL BUTYLCARBAMATE	GHS06, GHS05, GHS09, GHS08 Dgr Acute Tox. 4, H302 Skin Sens. 1, H317 Eye Dam. 1, H318 Acute Tox. 3, H331 STOT RE 1, H372 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 10		0.1 <= x % < 1

(Full text of H-phrases: see section 16)

Information on ingredients :

- [1] Substance for which maximum workplace exposure limits are available.
- [6] Substances of very high concern (SVHC).

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.
If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.
Do not proceed with mouth-to-mouth or mouth-to-nose resuscitation. Use the appropriate equipment.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.
If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.
Watch out for any remaining product between skin and clothing, watches, shoes, etc.
In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.
In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

ALSAN FLASHING QUADRO

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- foam
- powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

Contaminated areas must be cleaned very quickly.

A possible decontaminant for flammable products may be : (expressed by volume) water (45 parts), ethanol or isopropanol (50 parts), concentrated ammonia (d-0.880) (5 parts). For non-flammable products: sodium carbonate (5 parts), water (95 parts).

This residue must be stored for disposal in compliance with current regulations (see section 13).

ALSAN FLASHING QUADRO

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically non-conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Avoid exposure - obtain special instructions before use.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

ALSAN FLASHING QUADRO

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
1330-20-7	221	50	442	100	Peau
100-41-4	442	100	884	200	Peau
1305-78-8	1	-	4	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1330-20-7	50 ppm 220 mg/m ³	100 ppm 441 mg/m ³		Sk. BMGV	
100-41-4	100 ppm 441 mg/m ³	125 ppm 552 mg/m ³		Sk	
1305-78-8	- ppm 2 mg/m ³	- ppm - mg/m ³			
4098-71-9	0.02 mg/m ³	0.07 mg/m ³	-	-	-

- Ireland (Code of practice for the Chemical Agents Regulations, 2016) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1330-20-7	50 ppm 221 mg/m ³	100 ppm 442 mg/m ³			
100-41-4	100 ppm 442 mg/m ³	200 ppm 884 mg/m ³			
1305-78-8	2 mg/m ³				
4098-71-9	0.005 ppm				

- Malta (L.N. 353/2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1330-20-7	50 ppm 221 mg/m ³	100 ppm 442 mg/m ³		Skin	
100-41-4	100 ppm 442 mg/m ³	200 ppm 884 mg/m ³		Skin	

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE (CAS: 4098-71-9)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Inhalation.
Short term local effects.
0.0453 mg of substance/m³

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term local effects.
0.0453 mg of substance/m³

HEXAMETHYLENE DIISOCYANATE, OLIGOMERS (CAS: 28182-81-2)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Inhalation.
Short term local effects.
1 mg of substance/m³

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term local effects.
0.5 mg of substance/m³

MORPHOLINE-4-CARBALDEHYDE (CAS: 4394-85-8)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term local effects.
0.293 mg of substance/cm²

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
98 mg of substance/m³

ALSAN FLASHING QUADRO**Final use:**

Exposure method:
Potential health effects:
DNEL :

Consumers.

Ingestion.
Long term systemic effects.
8 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Long term systemic effects.
8 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
29 mg of substance/m3

OXYDE DE CALCIUM (CAS: 1305-78-8)**Final use:**

Exposure method:
Potential health effects:
DNEL :

Workers.

Inhalation.
Short term local effects.
4 mg of substance/m3

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term local effects.
1 mg of substance/m3

Final use:

Exposure method:
Potential health effects:
DNEL :

Consumers.

Inhalation.
Short term local effects.
4 mg of substance/m3

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term local effects.
1 mg of substance/m3

Predicted no effect concentration (PNEC):**3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE (CAS: 4098-71-9)**

Environmental compartment: Soil.
PNEC : 44.01 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.06 mg/l

Environmental compartment: Sea water.
PNEC : 0.003 mg/l

Environmental compartment: Intermittent waste water.
PNEC : 0.04 mg/l

Environmental compartment: Fresh water sediment.
PNEC : 218.92 mg/kg

Environmental compartment: Marine sediment.
PNEC : 21.89 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 10.6

HEXAMETHYLENE DIISOCYANATE, OLIGOMERS (CAS: 28182-81-2)

Environmental compartment: Soil.
PNEC : 53.2 g/kg

ALSAN FLASHING QUADRO

Environmental compartment: PNEC :	Fresh water. 127 µg/l
Environmental compartment: PNEC :	Sea water. 12.7 µg/l
Environmental compartment: PNEC :	Intermittent waste water. 1270 µg/l
Environmental compartment: PNEC :	Fresh water sediment. 266.7 g/kg
Environmental compartment: PNEC :	Waste water treatment plant. 38.28 mg/l

MORPHOLINE-4-CARBALDEHYDE (CAS: 4394-85-8)

Environmental compartment: PNEC :	Fresh water. 0.5 mg/l
Environmental compartment: PNEC :	Sea water. 0.05 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 5 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 1.85 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.0764 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 2000 mg/l

OXYDE DE CALCIUM (CAS: 1305-78-8)

Environmental compartment: PNEC :	Soil. 817.4 mg/kg
Environmental compartment: PNEC :	Fresh water. 0.37
Environmental compartment: PNEC :	Sea water. 0.24
Environmental compartment: PNEC :	Intermittent waste water. 0.37
Environmental compartment: PNEC :	Waste water treatment plant. 2.27

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.
Store personal protective equipment in a clean place, away from the work area.

ALSAN FLASHING QUADRO

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Antistatic gloves in accordance with standard EN1149

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear antistatic clothing made from heat resistant natural or synthetic fibres in accordance with standard EN1149.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A2 (Brown)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Viscous liquid.

Important health, safety and environmental information

pH : Not relevant.
Boiling point/boiling range : Not relevant.
Flash Point : 34.00 °C.
Vapour pressure (50°C) : Below 110 kPa (1.10 bar).
Density : 1.14
Water solubility : Insoluble.
Viscosity : 10 000 mPa.s
Melting point/melting range : Not relevant.
Self-ignition temperature : Not relevant.
Decomposition point/decomposition range : Not relevant.

ALSAN FLASHING QUADRO

9.2. Other information

VOC (g/l) : 245

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

Keep away from oxidising agents and strongly acidic or basic materials to avoid exothermic reactions.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

The mixture can also release hydrogen cyanide, amines and alcohols.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces
- humidity

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Harmful by inhalation.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

May cause an allergic reaction by skin contact.

Based on isocyanate properties and considering the toxicological data of similar mixtures, this preparation may cause irritations and/or sensitisations of the respiratory system.

It may therefore bring about asthma, respiratory difficulties and angina pectoris.

Those susceptible may display asthmatic symptoms when exposed to atmospheres with an isocyanate concentration well below those of the VLE : exposure limits.

Repeated exposure may cause permanent respiratory problems.

May cause severe damage to organs in the event of repeated or prolonged exposure.

11.1.1. Substances

Acute toxicity :

3-IODO-2-PROPYNYL BUTYLCARBAMATE (CAS: 55406-53-6)

Oral route : LD50 = 400 mg/kg
Species : Rat
OECD Guideline 423 (Acute Oral toxicity Acute Toxic Class Method)

Dermal route : LD50 > 5000 mg/kg

ALSAN FLASHING QUADRO

Species : Rat
 OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (n/a) : LC50 = 0.67 mg/l
 Species : Rat
 OECD Guideline 403 (Acute Inhalation Toxicity)
 Duration of exposure : 4 h

PRÉPOLYMÈRE D'OXYDE DE PROPYLÈNE, D'OXYDE D'ÉTHYLÈNE ET DE DIISOCYANATE DE TOLUÈNE (PTMGE) (CAS: 68132-86-5)

Oral route : LD50 > 5000 mg/kg
 Species : Rat

Dermal route : LD50 > 5000 mg/kg
 Species : Rabbit

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE (CAS: 4098-71-9)

Oral route : LD50 = 4814 mg/kg
 Species : Rat

Dermal route : LD50 > 7000 mg/kg
 Species : Rat
 OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (n/a) : LC50 = 0.031 mg/l
 Species : Rat
 OECD Guideline 403 (Acute Inhalation Toxicity)
 Duration of exposure : 4 h

HEXAMETHYLENE DIISOCYANATE, OLIGOMERS (CAS: 28182-81-2)

Oral route : LD50 > 2500 mg/kg
 Species : Rat
 OECD Guideline 423 (Acute Oral toxicityAcute Toxic Class Method)

Dermal route : LD50 > 2000 mg/kg
 Species : Rat
 OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (n/a) : LC50 = 0.39 mg/l
 Species : Rat

OXYDE DE CALCIUM (CAS: 1305-78-8)

Oral route : LD50 > 2000 mg/kg
 Species : Rat
 OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)

Dermal route : LD50 > 2500 mg/kg
 Species : Rabbit
 OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/skin irritation :

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE (CAS: 4098-71-9)
 Species : Rabbit
 OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Respiratory or skin sensitisation :

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE (CAS: 4098-71-9)
 Guinea Pig Maximisation Test (GMPT) : Sensitiser.
 Species : Guinea pig

ALSAN FLASHING QUADRO

OECD Guideline 406 (Skin Sensitisation)

11.1.2. Mixture

Serious damage to eyes/eye irritation :

The irritant classification based on a high/low pH has been confirmed by irritation tests.

Respiratory or skin sensitisation :

Contains isocyanates. May cause an allergic reaction.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

3-IODO-2-PROPYNYL BUTYLCARBAMATE (CAS: 55406-53-6)

Fish toxicity : LC50 = 0.067 mg/l
Species : *Oncorhynchus mykiss*
Duration of exposure : 96 h
OECD Guideline 203 (Fish, Acute Toxicity Test)

NOEC = 0.0084 mg/l
Factor M = 10
Species : *Pimephales promelas*
Duration of exposure : 35 days

Crustacean toxicity : EC50 = 0.16 mg/l
Species : *Daphnia magna*
Duration of exposure : 48 h
OECD Guideline 202 (*Daphnia* sp. Acute Immobilisation Test)

NOEC = 0.05 mg/l
Factor M = 1
Species : *Daphnia magna*
Duration of exposure : 21 days

Algae toxicity : ECr50 = 0.022 mg/l
Species : *Scenedesmus subspicatus*
Duration of exposure : 72 h
OECD Guideline 201 (Alga, Growth Inhibition Test)

NOEC = 0.0046 mg/l
Factor M = 10
Species : *Scenedesmus subspicatus*
Duration of exposure : 72 h

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE (CAS: 4098-71-9)

Fish toxicity : LC50 > 208 mg/l
Species : *Cyprinus carpio*
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 27 mg/l
Species : *Daphnia magna*
Duration of exposure : 48 h

Algae toxicity : ECr50 > 4.4 mg/l
Species : *Desmodesmus subspicatus*
Duration of exposure : 72 h

ALSAN FLASHING QUADRO

HEXAMETHYLENE DIISOCYANATE, OLIGOMERS (CAS: 28182-81-2)

Fish toxicity : LC50 = 8.9 mg/l
Species : Brachydanio rerio
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 127 mg/l
Species : Daphnia magna
Duration of exposure : 48 h

Algae toxicity : ECr50 > 1000 mg/l
Species : Desmodesmus subspicatus
Duration of exposure : 72 h

OXYDE DE CALCIUM (CAS: 1305-78-8)

Fish toxicity : LC50 = 50.6 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 49.1 mg/l
Duration of exposure : 48 h

Algae toxicity : ECr50 = 184.57 mg/l
Duration of exposure : 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

3-IODO-2-PROPYNYL BUTYLCARBAMATE (CAS: 55406-53-6)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

PRÉPOLYMÈRE D'OXYDE DE PROPYLÈNE, D'OXYDE D'ÉTHYLÈNE ET DE DIISOCYANATE DE TOLUÈNE (PTMGE) (CAS: 68132-86-5)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE (CAS: 4098-71-9)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

HEXAMETHYLENE DIISOCYANATE, OLIGOMERS (CAS: 28182-81-2)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

OXYDE DE CALCIUM (CAS: 1305-78-8)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

ETHYLBENZENE (CAS: 100-41-4)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

XYLENE (CAS: 1330-20-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

12.3.1. Substances

3-IODO-2-PROPYNYL BUTYLCARBAMATE (CAS: 55406-53-6)

ALSAN FLASHING QUADRO

Octanol/water partition coefficient : log K_{ow} = 2.8

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE (CAS: 4098-71-9)
Octanol/water partition coefficient : log K_{ow} = 4.75

HEXAMETHYLENE DIISOCYANATE, OLIGOMERS (CAS: 28182-81-2)
Octanol/water partition coefficient : log K_{ow} = 7.8

Bioaccumulation : BCF = 3.2
Species : Brachydanio rerio (Fish)

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 2 : Hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2020).

14.1. UN number

1263

14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

- Classification :



3

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	5 L	163 367 650	E1	3	D/E

ALSAN FLASHING QUADRO

If Q <450l, see 2.2.3.1.5.1.

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	3	-	III	5 L	F-E, S-E	163 223 367 955	E1	Category A	-

if Q < 450 l see IMDG 2.3.2.5.

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	III	355	60 L	366	220 L	A3 A72 A192	E1
	3	-	III	Y344	10 L	-	-	A3 A72 A192	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)
- New Zealand HSNO: Surface Coatings and Colourants (flammable) Group Standard 2020 - HSR 00 2662

- Container information:

No data available.

- Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) :

The permitted European level of VOC in this ready-to-use product is limited to 245 g/l.

The permitted European levels of VOC in the ready-to-use product (category IIAi) are 600 g/l maximum in 2007 and 500 g/l maximum in 2010.

- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) :

WGK 2 : Hazardous for water.

- Swiss ordinance on the incentive tax on volatile organic compounds :

- 108-65-6 acétate de 1-méthoxy-2-propyle
- 108-65-6 acétate de 1-méthoxy-2-propyle
- 108-65-6 acétate de 1-méthoxy-2-propyle
- 100-41-4 éthylbenzène
- 1330-20-7 xylènes (mélanges d'isomères)
- 1330-20-7 xylènes (mélanges d'isomères)

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.

ALSAN FLASHING QUADRO

H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure .
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

UFI : Unique Formula Identifier

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.