



## GHS MINI

## Equus Traxx Solvent Sealer

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	20-40	350 mg/m3
naphtha petroleum, light aromatic solvent	64742-95-6.	20-40	-

GHS	DG
	 <p>UN No: <b>1993</b>            Hazchem Code: <b>•3Y</b>            DG Class: <b>3</b>            Subsidiary Hazard: <b>Not Applicable</b>            Packing Group: <b>III</b>            Poisons Schedule: <b>S5</b></p>

## Precautionary statements(s): Response

In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Collect spillage.

IF ON SKIN: Wash with plenty of water and soap.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

## Precautionary statements(s): Storage

Store in a well-ventilated place. Keep cool.

Store locked up.

## Precautionary statements(s): Disposal

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

## HEALTH HAZARD INFORMATION



Signal word: **Warning**

Hazard statement(s):

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H402 Harmful to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.

## PRECAUTIONS FOR USE



## Precautionary statements(s): General

Not Applicable

## Precautionary statements(s): Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use only a well-ventilated area.

Ground and bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Avoid breathing mist/vapours/spray.

Avoid release to the environment.

Wear protective gloves, protective clothing, eye protection and face protection.

Wash all exposed external body areas thoroughly after handling.