

Hazardous, NON-Dangerous Goods

SDS 442a

Reference No:

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Monopur SL Part A

Recommended use: No Information

Supplier: Equus Industries Ltd

Company No.:

Street Address: Sheffield Street, Riverlands

PO Box 601 Blenheim

Telephone: +64 3 578 0214 info@equus.nz

Emergency Telephone number: National Poisons Centre 0800 764 766

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of EPA New Zealand GHS 7.

EPA Group Standard: HSR002670 - Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020



Signal Word

Warning

Hazard Classification

Sensitisation - Skin - Category 1

Hazard Statement

H317 May cause an allergic skin reaction.

Prevention Precautionary Statements

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust, fume, gas, mist, vapours or spray.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing including eye/face protection.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P321 Specific treatment (see on product label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Storage Precautionary Statement

Not allocated

Disposal Precautionary Statement

Product Name: Monopur SL Part A

P501 Dispose of contents/container in accordance with local, regional, national and

Issued: 2024-04-10 Version: 1.2 Page 1 of 8



international regulations.

DANGEROUS GOOD CLASSIFICATION

A COMPOSITION INFORMATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION		
CHEMICAL ENTITY	CAS NO	PROPORTION
1,2-Ethanediol	107-21-1	2.5-10 %
Solvent naphtha, petroleum, light aromatic	64742-95-6	0.1-1.0 %
Dipentene	138-86-3	0.1-1.0 %
Cyclohexene, 1-methyl-4-(1-methylethylidene)-	586-62-9	0.1-1.0 %
Nitric acid, magnesium salt	10377-60-3	<0.1 %
Formaldehyde	50-00-0	<0.1 %
mixture of: 5-chloro-2-methyl-2h-isothiazol-3-one [ec no 247-500-7] and 2-methyl-2hisothiazol-3-one [EC no. 220-239-6] (3:1)	55965-84-9	<0.1 %
Ingredients determined to be Non-Hazardous		Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Move to fresh air. Consult a physician after significant exposure.

Skin Contact: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist

Ingestion: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

PPE for First Aiders: Wear overalls, gloves, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.4.2 Most important symptoms and effects, both acute and delayed. No Information4.3 Indication of any immediate medical attention and special treatment needed. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. FIRE FIGHTING MEASURES

Product Name: Monopur SL Part A Reference No:

Issued: 2024-04-10 Version: 1.2 Page 2 of 8



Reference No:

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations After cleaning, flush away traces with water.

LARGE SPILLS

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations After cleaning, flush away traces with water.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable

7. HANDLING AND STORAGE

Handling: Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment

Storage: Do not freeze. Keep tightly closed in a dry, cool and well-ventilated place. Keep locked up or in an area accessible only to qualified or authorised persons.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Ethylene glycol (vapour and mist)	Ceiling - 50	Ceiling - 127			
Formaldehyde	0.3		0.6		carc cat 1; dsen

As published by WorkSafe New Zealand.

Product Name: Monopur SL Part A

WES-TWA (Workplace Exposure Standard - Time-weighted average). The average airborne concentration of a substance calculated over an eight-hour working day.

WES-Ceiling (Workplace Exposure Standard - Ceiling). A concentration that should not be exceeded at any time during any part of the working day.

WES-STEL (Workplace Exposure Standard - Short-term exposure limit). The 15-minute time weighted average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-

Issued: 2024-04-10 Version: 1.2 Page 3 of 8



weighted average exposures apply. Exposures at concentrations between the WES-TWA and the WES-STEL should be less than 15 minutes, should occur no more than four times per day, and there should be at least 60 minutes between successive exposures in this range.

ppm Parts of vapour or gas per million of air by volume.

mg/m3 Milligrams of substance per cubic metre of air.

r The value for respirable dust.

carc cat 1 Known or presumed human carcinogen.

sen Sensitiser.

dsen Dermal sensitiser.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the WorkSafe New Zealand the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. When using this material, use explosive dust handling controls to minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks and flame; prevent the build-up of static charges with appropriate earthing of equipment and personnel.

Personal Protection Equipment: OVERALLS, GLOVES, CHEMICAL GOGGLES, RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear overalls, gloves, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

RECOMMENDATIONS FOR CONSUMER USE:

RESPIRATORY PROTECTION: In case of insufficient ventilation wear suitable respiratory equipment.EYE PROTECTION: Tightly fitting safety goggles.HAND PROTECTION: Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.OTHER PROTECTIVE EQUIPMENT: No InformationENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

Hygiene measures: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Base Units: Kilogram

Product Name: Monopur SL Part A Reference No:

Issued: 2024-04-10 Version: 1.2 Page 4 of 8



Form: Liquid

Colour: Not determined

Odour: Slight

Solubility:EmulsionSolubility in water:EmulsionSpecific Gravity:0.120Density:1.03

Relative Vapour Density (air=1): Not determined Vapour Pressure: Not determined

Flash Point (°C):

Explosion/Flammability Limits:

Autoignition Temperature (°C):

Melting Point/Range (°C):

Pour Point/Range (°C):

Boiling Point/Range (°C):

Not determined
Not determined
126 - 102

Decomposition Point (°C): Not determined Sublimation Point (°C): Not determined **Dropping Point (°C):** Not determined pH: Not determined Viscosity: Not determined **Surface Tension:** Not determined **Evaporation Rate (n-Butyl acetate=1):** Not determined **Partition Coefficient:** Not determined

Total VOC (g/Litre): 0

Odour Threshold:

Explosive properties:

Oxidising properties:

Volatile by Volume:

Molecular Formula:

Molecular Weight:

Not determined

Not determined

Not determined

Not determined

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions.

Conditions to avoid: Direct sources of heat.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

Hazardous reactions: No reactivity hazards known under normal storage and use conditions. Hazardous polymerisation does not occur.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: No information available.

Product Name: Monopur SL Part A

Reference No:

Issued: 2024-04-10 Version: 1.2 Page 5 of 8



Skin contact: No information available. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: No information available.

Eye contact: No information available.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): $LC_{50} > 20.0 \text{ mg/L}$ for vapours or $LC_{50} > 5.0 \text{ mg/L}$ for dust and mist.

Solvent naphtha (petroleum), light arom. LC50 (Rat): 3670 ppm/8 hours (Method: Vapor)

Magnesium Nitrate LC50 (Rat): 23.4 mg/l/4/h (Method: Vapor)

Formaldehyde LC50 (Rat): 250 - 590 mg/cu m (Method: Vapor)

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3- one [ec no 247-500-7] and 2-methyl-2h isothiazol-3-one [EC no.

220-239-6] (3:1) LC50 (Rat): 0.33 mg/L (Method: (inh/4h/rat - dust) Vapor)

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg}$ bw

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3- one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-one [EC no.

220-239-6] (3:1) LD50 (Rabbit): 87.12 mg/kg (Method: Dermal)

Solvent naphtha (petroleum), light arom LD50 (Rat): >2000 mg/kg (Method: Dermal)

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000 \text{ mg/Kg bw}$

Solvent naphtha (petroleum), light arom. LD50 (Rat): 4700 mg/kg (Method: Oral)

Magnesium Nitrate LD50 (Rat): 10760 mg/kg (Method: Oral)

Formaldehyde LD50 (Rat): 100 mg/kg (Method: Oral)

Mixture of: 5-chloro-2-methyl-2h-isothiazol-3- one [ec no 247-500-7] and 2-methyl-2h isothiazol-3-one [EC no.

220-239-6] (3:1) LD50 (Rat): 64 mg/kg (Method: Oral)

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure): This material has been classified as not a specific hazard to target organs by a single exposure.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: No information

Product Name: Monopur SL Part A Reference No:

Issued: 2024-04-10 Version: 1.2 Page 6 of 8



Solvent naphtha (petroleum), light arom 48hr EC50 (Daphnia magna): >1 - 10 mg/l Solvent naphtha (petroleum), light arom 72hr IC50 (algae): >1-10 mg/l Solvent naphtha (petroleum), light arom. 96hr LC50 (fish): >10-100 mg/l mixture of: 5-chloro-2-methyl-2h-isothiazol-3- one [ec no 247-500-7] and 2-methyl-2h-isothiazol-3-one [EC no. 220-239-6] (3:1) 96hr LC50 (rainbow trout): 0.19 mg/L

Chronic aquatic hazard: This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log Kow < 4.No information

Ecotoxicity in the soil environment: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial vertebrates: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial invertebrates: This material has been classified as non-hazardous.

Ecotoxicity: No information

Persistence and degradability: No information

Bioaccumulative potential: No information

Mobility: No information

13. DISPOSAL CONSIDERATIONS

WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Waste codes should be assigned by the user based on the application for which the product was used. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

Product Name: Monopur SL Part A Reference No:

Issued: 2024-04-10 Version: 1.2 Page 7 of 8



EPA Group Standard: HSR002670 - Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020

16. OTHER INFORMATION

Reason for issue: Revised

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

Product Name: Monopur SL Part A Reference No:

Issued: 2024-04-10 Version: 1.2 Page 8 of 8