

Safety Data Sheet



Hazardous, Dangerous Goods

SDS 459

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **DURACON BFK**

Recommended use: Binder

Supplier: Equus Industries Ltd
Company No.:
Street Address: Sheffield Street, Riverlands
PO Box 601
Blenheim
Telephone: +64 3 578 0214
Email: info@equus.nz

Emergency Telephone number: **National Poisons Centre 0800 764 766**

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of EPA New Zealand GHS 7.

EPA Group Standard: HSR002662 - Surface Coatings and Colourants (Flammable) Group Standard 2020



Signal Word

Danger

Hazard Classifications

Flammable Liquids - Category 2
Skin Corrosion/Irritation - Category 2
Sensitisation - Skin - Category 1
Specific Target Organ Toxicity following Single Exposure - Category 3 - Respiratory Tract Irritation
Long Term Hazards to the Aquatic Environment - Category 3

Hazard Statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H413 May cause long lasting harmful effects to aquatic life.

Prevention Precautionary Statements

P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical, ventilating, lighting and all other equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust, fume, gas, mist, vapours or spray.
P264 Wash hands, face and all exposed skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.

Product Name: **DURACON BFK**

Reference No:

Issued: 2024-01-24

Version: 1.2

Page 1 of 9

Safety Data Sheet



P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing including eye/face protection.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 Take off contaminated clothing.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire: Use (insert appropriate media) to extinguish.

Storage Precautionary Statements

P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 3

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	25 - 50 %
2-ETHYLHEXYL ACRYLATE	103-11-7	25 - 50 %
TRIETHYLENGLYCOL DIMETHACRYLATE	109-16-0	1 - 2.5 %
Silica, amorphous, fumed, crystalline free	112945-52-5	1 - <5 %
2-(N-METHYL-P-TOLUIDIN O)ETHANOL	2842-44-6	0,1 - <1 %
Ingredients determined to be Non-Hazardous		Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact: Effects may be delayed. If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital.

Safety Data Sheet



Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

PPE for First Aiders: Wear gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed.

5. FIRE FIGHTING MEASURES

Hazchem Code: •3YE

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: 14

7. HANDLING AND STORAGE

Handling: Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Provide exhaust ventilation close to floor level. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Open drum carefully as content may be under pressure. Use only in well-ventilated areas. Vapours may form explosive mixtures with air. Keep product and empty container away from heat and sources of ignition. Take measures to prevent the build up of electrostatic charge. Do not use sparking tools. Use only explosion-proof equipment. Have fire extinguishers ready before opening the drum.

Storage: Store in original container. Never fill containers more than 80 % because aerial oxygen is necessary for stabilising. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep in an area equipped with solvent resistant flooring. Do not store together with oxidizing and

Safety Data Sheet



self-igniting products.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and/or the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Methyl methacrylate	50	208	100	416	skin; dsen

As published by WorkSafe New Zealand.

WES-TWA (Workplace Exposure Standard - Time-weighted average). The average airborne concentration of a substance calculated over an eight-hour working day.

WES-Ceiling (Workplace Exposure Standard - Ceiling). A concentration that should not be exceeded at any time during any part of the working day.

WES-STEL (Workplace Exposure Standard - Short-term exposure limit). The 15-minute time weighted average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Exposures at concentrations between the WES-TWA and the WES-STEL should be less than 15 minutes, should occur no more than four times per day, and there should be at least 60 minutes between successive exposures in this range.

ppm Parts of vapour or gas per million of air by volume.

mg/m3 Milligrams of substance per cubic metre of air.

skin Skin absorption.

sen Sensitiser.

dsen Dermal sensitiser.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the WorkSafe New Zealand the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator.

Personal Protection Equipment: GLOVES, SAFETY GLASSES, RESPIRATOR.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with

Safety Data Sheet



the work as identified by the risk assessment conducted.

Wear gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

RECOMMENDATIONS FOR CONSUMER USE:

Eye/Face Protection Tightly fitting safety goggles. Eye wash bottle with pure water. Hand Protection Solvent-resistant gloves. Suitable material: butyl-rubber. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Follow the skin protection plan. Skin and body protection Follow the skin protection plan. Flame retardant antistatic protective clothing. Remove and wash contaminated clothing before re-use. Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Preferably a compressed airline breathing apparatus. Hygiene measures Handle in accordance with good industrial hygiene and safety practice. When using, do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs. Keep working clothes separately. Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. When using, do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs. Keep working clothes separately.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid
Colour: Violet
Odour: acrylic-like

Solubility:	No information available
Solubility in water:	Insoluble
Specific Gravity:	No information available
Density:	0.98 g/cm ³ (25 °C)
Relative Vapour Density (air=1):	1.0
Vapour Pressure:	38.7 mbar (MMA)
Flash Point (°C):	12 °C (MMA) / 54 °F
Flammability Limits (%):	No information available
Autoignition Temperature (°C):	No information available
Melting Point/Range (°C):	-48 °C (MMA) / -54 °F
Boiling Point/Range (°C):	101 °C (MMA) / 214 °F
pH:	No information available
Viscosity:	130 - 170 mPa.s (25 °C)
Partition Coefficient:	1.38 log POW (MMA)
Total VOC (g/Litre):	No information available
Explosive properties:	Upper - 12.5 Vol.% (MMA) Lower 2.1 Vol.% (MMA) -

(Typical values only - consult specification sheet)

N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal conditions.

Conditions to avoid: Heat, flames and sparks. Exposure to sunlight.

Incompatible materials: void radical-forming starting agents, peroxides and reactive metals, Amines, Heavy metal compounds, Oxidizing agents, Reducing agents

Safety Data Sheet



Hazardous decomposition products: No hazardous decomposition products are known

Hazardous reactions: Polymerisation occurs when exposed to white light, ultraviolet light or heat. Polymerisation is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Irritating to mucous membranes. May cause respiratory irritation.

Skin contact: Causes skin irritation. May cause an allergic skin reaction. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: May be an eye irritant.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): $LC_{50} > 20.0$ mg/L for vapours or $LC_{50} > 5.0$ mg/L for dust and mist.

METHYL METHACRYLATE LC_{50} (Rat): 29.8 mg/l (Method: inhalation)

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000$ mg/Kg bw

METHYL METHACRYLATE LD_{50} (Rabbit): > 5000 mg/kg (Method: dermal)

2-ETHYLHEXYL ACRYLATE LD_{50} (Rabbit): = 7522 mg/kg (Method: dermal)

Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): $LD_{50} > 2,000$ mg/Kg bw

METHYL METHACRYLATE LD_{50} (Rat): > 5000 mg/kg (Method: oral)

2-ETHYLHEXYL ACRYLATE LD_{50} (Rat): 4435 mg/kg (Method: oral)

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes. Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure): This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in respiratory irritation.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Safety Data Sheet



Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: Harmful to aquatic life with long lasting effects < 1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chronic aquatic hazard: This material has been classified as a Category Chronic 3 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 10 - 100 mg/L, where the substance is not rapidly degradable and/or BCF \geq 500 and/or log K_{ow} \geq 4. Harmful to aquatic life with long lasting effects < 1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Ecotoxicity in the soil environment: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial vertebrates: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial invertebrates: This material has been classified as non-hazardous.

Ecotoxicity: No information available.

Persistence and degradability: Partially biodegradable

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Dispose of as hazardous waste in compliance with local and national regulations. Contaminated packaging - Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not burn, or use a cutting torch on, the empty drum. Waste Code. 150110 - packaging containing residues of or contaminated by dangerous substances.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



UN No:	1866
Dangerous Goods Class:	3
Packing Group:	II
Hazchem Code:	•3YE
Emergency Response Guide No:	14
Limited Quantities	5 L

Safety Data Sheet



Proper Shipping Name: RESIN SOLUTION

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



UN No: 1866
Dangerous Goods Class: 3
Packing Group: II
Limited Quantities: 5 L
Proper Shipping Name: RESIN SOLUTION

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 1866
Dangerous Goods Class: 3
Packing Group: II
Limited Quantities: 1 L
Proper Shipping Name: RESIN SOLUTION

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

- Montreal Protocol (Ozone depleting substances)
- The Stockholm Convention (Persistent Organic Pollutants)
- The Rotterdam Convention (Prior Informed Consent)
- Basel Convention (Hazardous Waste)
- International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

EPA Group Standard: HSR002662 - Surface Coatings and Colourants (Flammable) Group Standard 2020

16. OTHER INFORMATION

Reason for issue: Minor Text Changes

Safety Data Sheet



This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.