

SDS 708

# MATERIAL SAFETY DATA SHEET

PAGE 1 OF 6

1.1       PRODUCT NAME:       THERMEXX DETAIL PLASTER         1.2       USE OF PRODUCT       Trowel applied, water based synthetic detailing plast interior and exterior use.         1.3       SUPPLIER:       Equus Industries Ltd Sheffield Street Riverlands Industrial Estate Blenheim, Marlborough, New Zealand Telephone: +64 3 578 0214 Fax: +64 3 578 0919 Email: admin@equus.co.nz         1.4       EMERGENCY CONTACT:       National Poison Centre Telephone: 0800 764 766         Information about Safety Data Sheet: Telephone: +64 3 578 0214       8:00am – 6:00pm Mon – Fri         1.5       Date of Preparation:       12 June 2020         2.       Hazards Identification         4.1       Classified as hazardous according to New Zealand Hazardous substances (min degrees of hazard) Regulations 2017         2.2       DG Status:	ar for		
1.3       SUPPLIER:       Equus Industries Ltd Sheffield Street Riverlands Industrial Estate Blenheim, Marlborough, New Zealand Telephone: +64 3 578 0214 Fax: +64 3 578 0919 Email: admin@equus.co.nz         1.4       EMERGENCY CONTACT:       National Poison Centre Telephone: 0800 764 766         Information about Safety Data Sheet: Telephone: +64 3 578 0214       8:00am – 6:00pm Mon – Fri         1.5       Date of Preparation:       12 June 2020         2.       Hazards Identification         2.1       Classification: HSNO Status:       Classified as hazardous according to New Zealand Hazardous substances (min degrees of hazard) Regulations 2017	ar for		
Sheffield Street         Riverlands Industrial Estate         Blenheim, Marlborough, New Zealand         Telephone: +64 3 578 0214         Fax:       +64 3 578 0919         Email:       admin@equus.co.nz         1.4       EMERGENCY CONTACT:       National Poison Centre         Telephone:       0800 764 766         Information about Safety Data Sheet:       Telephone: +64 3 578 0214         8:00am - 6:00pm Mon - Fri       12 June 2020         2.       Hazards Identification         2.1       Classification:         HSNO Status:       Classified as hazardous         According to New Zealand Hazardous substances (mindegrees of hazard) Regulations 2017	Trowel applied, water based synthetic detailing plaster for interior and exterior use.		
Telephone: 0800 764 766         Information about Safety Data Sheet: Telephone: +64 3 578 0214       8:00am – 6:00pm Mon – Fri         1.5       Date of Preparation:       12 June 2020         2.       Hazards Identification         2.1       Classification: HSNO Status: Classified as hazardous according to New Zealand Hazardous substances (min degrees of hazard) Regulations 2017			
1.5       Date of Preparation:       12 June 2020         2.       Hazards Identification         2.1       Classification:         HSNO Status:       Classified as hazardous according to New Zealand Hazardous substances (min degrees of hazard) Regulations 2017			
<ul> <li>2. Hazards Identification</li> <li>2.1 Classification: HSNO Status: Classified as hazardous according to New Zealand Hazardous substances (mindegrees of hazard) Regulations 2017</li> </ul>	Information about Safety Data Sheet: Telephone: +64 3 578 0214 8:00am – 6:00pm Mon – Fri		
<ul> <li>Classification: HSNO Status: Classified as hazardous according to New Zealand Hazardous substances (mindegrees of hazard) Regulations 2017</li> </ul>			
HSNO Status: Classified as hazardous according to New Zealand Hazardous substances (mir degrees of hazard) Regulations 2017			
2.2 DG Status	imum		
Not classified as Dangerous Good under NZS 5433: 2012 Transport of Dangerous Goods on Land			
2.3 Hazard Classification:			
2.3.1 Class and GHS Category Skin Sensitisation Cat 3 Reproductive toxicity Cat 2			
2.3.2HSNO CategoryHazard Statement6.5BMay cause an allergic skin reaction			
6.8B Suspected of damaging fertility or the unborn child			
2.4 Signal Word: Warning			
2.5       Prevention Statements         P201       Obtain special instructions before use         P202       Do not handle until all safety precautions have been read and understood         P261       Avoid breathing dust/fume/gas/mist/vapours/spray         P280(protective gloves)       Wear protective gloves/protective clothing/eye protection/face protection         P281       Use personal protective equipment as required         Equus Industries Ltd, Sheffield Street, Riverlands Industrial Estate, Blenheim, Marlborough, New Zealand Telephone: +64 3 578 0214			



#### 2.6 Response Statements

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention
P363	Wash contaminated clothing before reuse
P308 + P313	IF exposed or concerned: Get medical advice/ attention

#### 2.6 Storage Statement

P405 Store locked up

#### 3. Composition/Information on Ingredients

#### **3.1 Chemical Characterization (Preparation):** This product is a preparation.

#### 3.2 Hazardous Ingredients:

CAS NO.	COMPONENT	CONCENTRATION (weight %)
25265-77-4	2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	<1.1
-	Acrylic emulsion (6.5B)	3.5
-	Non-hazardous ingredients	Balance

#### 4. First Aid Measures

#### 4.1 After Inhalation:

Remove person to fresh air.

# 4.2 After Skin Contact:

Wash with soap and water as a precaution. If skin irritation develops, consult a doctor.

### 4.3 After Eye Contact:

Rinse with plenty of water for at least 10 minutes, while holding eyelid open. Remove contact lenses, if present and easy to do. If eye irritation persists, consult a doctor.

### 4.4 After Ingestion:

Drink 1 or 2 glasses of water. Consult a doctor if necessary. Never give anything by mouth to an unconscious person.

# 5. Fire Fighting Measures

#### 5.1 Suitable Extinguishing Media:

Use extinguishing media appropriate for surrounding fire.

## 5.2 Protective Equipment:

Wear self contained breathing apparatus and protective suit.

# 5.3 Specific Hazards:

Dried product can burn.

### 5.4 Combustion Products:

Carbon monoxide, carbon dioxide, toxic fumes and smoke. May yield acrylic monomers.



# 6. Accidental Release Measures

### 6.1 **Preliminary Action and Precautions:**

- 6.1.1 Use personal protective equipment.
- 6.1.2 Keep people away from and upwind of spill/leak.
- 6.1.3 Material can create slippery conditions.
- 6.1.4 Contain spills immediately with inert materials (eg. sand, earth etc.)
- 6.1.5 Transfer liquids and solid diking material to suitable containers for recovery or disposal.
- 6.1.6 Keep spills and cleaning run off from entering sewers, drains and open bodies of water.

### 7. Handling and Storage

# 7.1 Handling:

- 7.1.1 Avoid contact with eyes, skin and clothing.
- 7.1.2 Wash hands thoroughly after handling.
- 7.1.3 Keep containers tightly closed when not in use.
- 7.1.4 Do not breathe vapours, mist or gas.

# 7.2 Storage:

- 7.2.1 Store in a cool well-ventilated space.
- 7.2.2 Keep containers tightly closed at all times.

# 8. Exposure Controls and Personal Protection Equipment

# 8.1 Exposure Limits:

No values assigned for this specific material.

### 8.2 Exposure Controls:

#### 8.2.1 Exposure Controls in the Work Place:

Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general, ventilation is inadequate

# 8.2.2 Personal Protection Equipment:

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure, then an approved respirator with a replaceable dust/particulate filter should be used. Reference should be made to Australia/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.



#### Eye Protection

Safety glassed with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australia/New Zealand Standard AS/NZS 1337 – Eye Protectors for Industrial Applications.

#### Hand Protection

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e methods of handling or according to risk assessments undertaken. References should be made to AS/NZS 2161.1: Occupational protective gloves – Selection, use and maintenance.

#### **Body Protection**

Suitable protective workwear e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial Clothing

#### 9. Physical and Chemical Properties

# 9.1 Information on basic physical and chemical properties:

mormation on basic physical and chemical pro	
Appearance:	Gritty paste
Colour	Green
Odour	Slightly ammoniacal
Odour Threshold	Not established
рН	8.0 -9.0
Melting point/freezing point	<0°C
Boiling Point/Range	>100°C
Flash Point	Not established
Evaporation rate	Not established
Flammability (solid, gas)	Not applicable
Upper/lower flammability or explosive limits	Not applicable
Vapour pressure	Not established
Vapour density	Not established
Relative density	1.7
Water Solubility(ies)	Dilutable/partially soluble
Water Solubility of ingredients	2,2,4-trimethyl-1,3-pentanediol
	monoisobutyrate 0.5-3.79g/l@25ºC
Partition Coefficient: n-octanol/water	Not established
Auto-ignition temperature	Not applicable
Decomposition temperature	Not established
Viscosity	Brookfield 50rpm, 16,800-36,000cps@23 <sup>0</sup> C

#### 10. Stability and Reaction

#### **10.1** General Information:

This product is stable, and no hazardous reactions are known.

# 10.2 Conditions to Avoid:

There are no known conditions which should be avoided.

#### 10.3 Material to Avoid:

There are no known materials which are incompatible with this product.

# **10.4** Hazardous Decomposition Products: None expected when material properly handled and stored. Thermal decomposition see section 5.

Equus Industries Ltd, Sheffield Street, Riverlands Industrial Estate, Blenheim, Marlborough, New Zealand Telephone: +64 3 578 0214 Fax: +64 3 5780919 Email: admin@equus.co.nz Web: www.equus.co.nz



	S	DS THERMEXX DETAIL	PLASTER Page 5 of 6
11.	Toxicological Information		
11.1	<b>General Information:</b> No specific data is available for this material.		
11.2	<b>Skin Contact:</b> May cause slight irritation to skin.		
11.3	<b>Eye Contact:</b> May cause slight irritation including redness and tear formation.		
11.4	<b>Ingestion:</b> May cause gastrointestinal discomfort. Symptoms may include nau	sea, vomiting, lethargy or	diarrhoea.
11.5	Inhalation: Inhalation may cause a slight irritation to the respiratory tract.		
12.	Ecological Information		
12.1	<b>Environment Protection:</b> Prevent from entering sewers, drains and waterways.		
12.2	<b>Ecotoxicity:</b> No product specific data available.		
12.3	<b>Persistence and degradability:</b> No product specific data available.		
12.4	<b>Bioacummulative Potential:</b> No product specific data available.		

#### 13. **Disposal Consideration**

#### 13.1 Material

Dispose of according to regulations by incineration in a special waste incinerator or landfill at a permitted facility in accordance with local/national regulations.

#### 14. **Transport Information**

- 14.1 Land Transport: Not regulated under NZS 5433 for land transport
- 14.2 Sea Transport: (IMO/IMDG): Not regulated
- 14.3 Air Transport: (IATA/ICAO): Not regulated

#### 15. **Regulatory Information**

#### 15.1 HSNO Approval:

Approved Code: HSNO Group Standard HSR002670 Surface Coatings and colourants (Subsidiary Hazard)

Equus Industries Ltd, Sheffield Street, Riverlands Industrial Estate, Blenheim, Marlborough, New Zealand Telephone: +64 3 578 0214 Fax: +64 3 5780919 Email: admin@equus.co.nz Web: www.equus.co.nz



16.	Other Information	
16.1	Hazard Classifications 6.5B 6.8B	Substances that are contact sensitisers. Substances that are suspected human reproductive or developmental toxicants
16.2	Abbreviations/Terminology: HSNO CAS WES TWA STEL	Hazardous substances and New Organisms Act Chemical Abstract Service Workplace Exposure Standard (Worksafe NZ) Time weighted average exposure level designed to protect from the effects of long-term exposure. Short-term Exposure Level (15 minutes)

### 16.3 Issue Information:

Date of Preparation:	12 June 2020
Reasons:	Update and format change
Replaces:	1 June 2007

**16.4** The information contained in this Data Sheet relates only to the specific material identified. Equus Industries Ltd believes the information to be accurate and reliable as at the date of this Data Sheet. No Warranty, Guarantee or representation is expressed or implied by the Company as to the absolute correctness or completeness of any representation contained in this Data and assumes no legal responsibility in connection therewith. It can not be assumed that all acceptable safety measures are contained in this Data Sheet, or that additional measures may not be required under particular or exceptional circumstances or conditions.