

FLAGMETAL STRIP

TPO roofing accessory - TPO membrane bonded to galvanised steel sheet

November 2024

DESCRIPTION:

The FLAGMETAL STRIP is made of galvanised steel coupled with FLAGON TPO membrane.

USE:

The FLAGMETAL STRIP is used on roofing as a fastening element for the closure of the verticals under the cap in waterproofing systems realised with FLAGON TPO synthetic membranes.

APPLICATION METHOD:

The FLAGMETAL STRIP is fixed with screws on the vertical. It is advisable to place appropriate sealing underneath. The FLAGON TOP membrane is welded with Leister hot air gun over the entire length of the FLAGMETAL STRIP.

CHARACTERISTIC:

Resistant to weathering and UV.

TECHNICAL DATA:

DEVELOPMENT		
Total development	-	50 mm
- development a	a	40 mm
- development b	b	5 mm
Total thickness	-	1.80 mm
- metal sheet thickness	-	0.60 mm
- TPO membrane thickness	-	1.20 mm

STORAGE AND PACKAGING:

Number of pieces for each pack	10
Weight	0.27 kg/m
Length	2 m
Colour	Sand grey

Note:

To be installed by an Equus Certified Applicator.

UNI EN ISO 9001:2000 (Quality Company System) and UNI EN ISO 14001 (environmental system) certified quality system.

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
--	----

MANUFACTURERS CONTACT DETAILS:

Manufacture location	Italy
Legal and trading name of manufacturer	Soprema New Zealand Limited
Manufacturer address for service	Level 3, Candida Building 4, 61 Constellation Drive, Mairangi Bay, Auckland 0630, New Zealand
Manufacturer website	www.soprema.com.au
Manufacturer email	info@soprema.com.au
Manufacturer phone number	+61 3 9221 6230
Manufacturer NZBN	9429050312962

