

BITUMEN ANGLE FILLETS

July 2024

BITUMEN ANGLE FILLETS:

A pre-manufactured, triangular angle fillet of rubber modified bitumen. This elastic fillet is used between horizontal and vertical parts or at details. It is compatible to all Equus bitumen waterproofing membranes.

ADVANTAGES:

- Quick and easy to install
- Permanent high elasticity at temperatures between 15°C and +90°C
- Perfect adhesion to many different construction materials such as plywood and concrete
- Light weight

SURFACE PREPARATION AND APPLICATION:

The surface shall be dry, clean and free of oil. The surface shall be primed with SOPRADERE QUICK or an Equus approved bitumen primer. Cut the fillet to the required length. Melt the sacrificial protective PE cover by torching or hot air welding. Press the fillet securely into the corner. The installation of the waterproofing membranes can proceed immediately.

DIMENSIONS:

2.5 cm X 2.5 cm X 3.5 cm
Length: 1.2 m

PACKAGING:

44 strips per box.

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
--	----



MANUFACTURERS CONTACT DETAILS:

Manufacture location	Turkey
Legal and trading name of manufacturer	Baumerk
Manufacturer address for service	Dursunköy Mah. Uygur Cad. No:44 34555 Hadımköy - Arnavutköy - İstanbul / TÜRKİYE
Manufacturer website	
Manufacturer email	info@baumerk.com
Manufacturer phone number	+90 212 438 7 888
Manufacturer NZBN	