

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without parameters.

DUO C-PROFILE

Aluminium bar for terminating waterproofing membranes

DESCRIPTION:

The C-PROFILE is a pre-manufactured profile that terminates the waterproofing membrane at the wall in a professional and watertight, wind-peel resistant manner.

The C-Profile is used at concrete or wooden walls and curbs.

ADVANTAGES:

- Increases the durability of the waterproofing system.
- Increases the bonding of the waterproofing to the wall or curb.
- Wind-peel resistant.
- Corrosion resistant.
- Continuous quality.
- Provides an aesthetical, straight finishing.
- Provides a dripping point off the wall.

TECHNICAL DATA:	
-----------------	--

Technical Characteristics	C-PROFILE
Material	Extruded aluminium profile (AI Mg Si 0.5 F22 quality)
Tensile strength	215 N/mm ²
Yield point	160 N/mm ²
Elongation	10%
Hardness	70 brinell
Length	2500 mm
Width	50 mm
Colour	Metalic
Characteristics tested according to German DIN 1748 sta	ndard.

INSTALLATION:

- The waterproofing is installed according to manufacturers details.
- The C-PROFILE is fastened at the edge of the waterproofing membrane into the wall.
- The C-PROFILE covers the membrane with 2/3 of its total width of 50 mm. The rest of the profile protrudes above the membrane.
- The space created at the top of the C-PROFILE is filled with a sealant compatible to the wall's material, bitumen and aluminium. SOPREMA recommends ALSAN MASTIC 2200 sealant.


WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004? No











January 2024





Page 2 of 2

DUO C-PROFILE

Aluminium bar for terminating waterproofing membranes

January 2024

MANUFACTURERS CONTACT DETAILS:

Manufacture location	Belgium
Legal and trading name of manufacturer	Soprema New Zealand Limited
Manufacturer address for service	Level 3, Candida Building 4, 61 Constellation Drive, Mairangi Bay, Auckland 0630, New Zealand
Manufacturer website	www.soprema.com.au
Manufacturer email	info@soprema.com.au
Manufacturer phone number	+61 3 9221 6230
Manufacturer NZBN	9429050312962

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.