



Roof Edge Profile Classic Plus

Description:

The Classic Plus roof edge profile is a pre-manufactured profile that terminates the waterproofing membrane at the highest edge of the roof in a professional, watertight and wind-uplift resistant manner.

The profile is used on top of roof edge curbs of wooden and concrete flat roofs.

Technical Characteristics:

Material:	Aluminium
Length per profile:	2500 mm
Width (visible, outside):	110 mm
Fastening zone	45 mm
Dripping edge:	15mm from wall


Advantages:

- Strong, stable and durable profile that increases the durability of the waterproofing system.
- Increases the bonding of the waterproofing to the edge of the roof deck.
- Special corner design to prevent penetration by horizontal driven rain.
- Available with connection plates, internal and external premanufactured welded corners.
- Wind uplift resistant.
- Corrosion resistant.
- Continuous aesthetical finish.
- Provides a dripping point of 15 mm off the wall to prevent water stains to the wall.



Installation:

- The waterproofing cap sheet is installed on the top of the roof edge curb.
- The profile is fastened at the roof edge on top of the cap sheet.
- The profile and its fixings are covered by another piece of cap sheet.
- Always refer to the manufacturer's detail drawing.



Туре	Α	в
110/60	110	60

Equus Industries Ltd PO Box 601 Blenheim Phone: 03 578 0214 Email: admin@equus.nz Website: www.equus.nz June 2021