

ISPC FASTENER

July 2024
PRODUCT DESCRIPTION:

This pre-assembled fastener is composed of a fastening plate sleeve and a nail. It fixes the waterproofing membrane and/or insulation.

BENEFITS:

- Fast and easy installation
- Pre-assembled in the factory
- High wind-uplift resistance
- Corrosion resistant
- Minimum 400 N pull-out strength per fastener


CHARACTERISTICS:

| | |
|---------------------------|--------------------------------|
| Material plate and sleeve | Polyamide (PA6) |
| Nail | Steel with Crapal zinc coating |
| Corrosion resistance nail | Minimum 15 Kesternich cycles |
| Length | 45 mm |
| Width plate | 50 mm |
| Colour | Blue plate and sleeve |
| Our reference | ISPC |

INSTALLATION:

- A hole of \varnothing 8 mm is drilled to the right depth into the concrete.
- The minimum insertion depth into the concrete is 35 mm.
- Drill minimum 10 mm more than the insertion depth for dust settlement.
- The length of the sleeve is minimum 35 mm more than the roof built-up.
- The fastener is inserted in the drilled hole.
- The fastener is tightened by knocking the nail into the sleeve with a rubber hammer.
- The fastener is located at the edge of the overlap of the waterproofing membrane as indicated by the waterproofing membrane's manufacturer.

WARNINGS AND BANS:

| | |
|--|----|
| Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004? | No |
|--|----|

MANUFACTURERS CONTACT DETAILS:

| | |
|--|---|
| Manufacture location | China |
| Legal and trading name of manufacturer | Soprema New Zealand Limited |
| Manufacturer address for service | Level 3, Candida Building 4, 61 Constellation Drive, Mairangi Bay, Auckland 0630, New Zealand |
| Manufacturer website | www.soprema.com.au |
| Manufacturer email | info@soprema.com.au |
| Manufacturer phone number | +61 3 9221 6230 |
| Manufacturer NZBN | 9429050312962 |