


Highly flexible tile adhesive



UNIFIX®-S3

Tile adhesive with very good working characteristics for the most challenging requirements.

Problems Solved.





VERY HIGH FLEXIBILITY

 **SCHOMBURG**

Highly flexible tile adhesive C2 TE S2 **UNIFIX®-S3**

Two-component, highly flexible and waterproof tile adhesive with decoupling effect and high deformation capability for secure laying of ceramic tiles and boards, porcelain stoneware, and large formats for wall and floor areas. The product-specific, highly flexible characteristics of UNIFIX-S3 enables secure laying of ceramic coverings on 'green' cement-based screed and concrete. In particular, the waterproof and stress-compensating mortar properties form the basis for secure adhesion in outdoor areas as AQUAFIN-TBS system component.






Areas of application

- UNIFIX-S3 is highly flexible and used as a thin-bed mortar, particularly for laying vitrified tiles with low water absorption $\leq 0.5\%$ (porcelain stoneware), stoneware, brick and mosaic on 'green' cement-based substrates.
- Thanks to the high deformation capability of UNIFIX-S3, damaging shear stresses in the covering can be largely compensated out and so it is also particularly well suited to use as a laying mortar for large formats.
- UNIFIX-S3 is particularly well suited to use on balconies and terraces, in swimming pools, on 'green' cement-based walkable substrates (cement-based screed approx. 3 days after laying).
- UNIFIX-S3 is suitable for mineral-based and dispersion-based SCHOMBURG compound seals.


Properties

- Two-component.
- Highly flexible.
- Waterproof and frost-resistant.
- For 'green' cement-based substrates.
- Compensates for stresses and has a decoupling effect.
- For heated substrates.
- For interior and exterior use.
- High bond shear strength.




The dependable solution for particular challenges. S2 tile adhesive for reliable tile laying.

Laying ceramic tiles, in some cases large-format tiled finishes, requires a particularly high level of safety in highly challenging areas, such as underwater and outdoor areas. UNIFIX-S3 is made from the combination of a powder component and a highly specialised liquid polymer component. This functional structure is the basis for a waterproof, highly elastic, and yet very strong tile adhesive - the highest level of 'know-how' and reliability.




High degree of polymer modification

Very flexible



Very resistant to slumping

For slippage-resistant tiling



Smooth application

Very convenient

SCHOMBURG GmbH & Co. KG
Aquafinstraße 2 - 8
D-32760 Detmold (Germany)
phone +49-5231-953-00
fax +49-5231-953-108
email export@schomburg.de
www.schomburg.com



 **SCHOMBURG**