ELASTOCOL STICK

Primer designed to enhance the adhesion of Soprema self-adhesive membranes

September 2026

DESCRIPTION:
ELASTOCOL STICK is composed of SBS synthetic rubbers, adhesive enhancing resins and volatile solvents. It is also suitable to prime non-porous surfaces such as concrete, fibre cement, metal and wood.

BRANZ Appraised
Appraisal No. 819

METHOD OF APPLICATION:
ELASTOCOL STICK can be applied with a brush, a roll or a spray can. Shake well before using.
It must be dry before applying the waterproofing membrane. Drying time will vary depending on air and surface temperature and humidity. Ensure primer is tacky to-the-touch but not wet before installing overlying membrane. Primer should not transfer to the fingertips when touched.

The application of primer should be limited to what can be covered with waterproofing membrane in one working day. Any areas not covered with membrane during the day must be reprimed - be sure to cover all open containers when not applying primer, as the primer is volatile. Application temperature above: -10°C

WARNING: Do not accelerate drying of ELASTOCOL STICK by heating with a torch.

PACKAGING:

Specifications	Elastocol Stick
Physical State	Liquid
Colour	Red
Coverage	Porous surfaces: 2-3 m^2/L (0.3 to 0.5 L/m^2)
	Non-porous surfaces: 4-6 m^2/L (0.1 to 0.17 L/m^2)
Packaging	19L
Pail per pallet	36

PROPERTIES:

Properties	Elastocol Stick
Specific gravity at 20°C	0.79 kg/l
Solids by weight	24%
Brookfield Viscosity 25°C	200 cP
Drying time	15 to 60 minutes, depending on temperature and quantity applied

STORAGE AND HANDLING:
Shelf life: Up to 60 months in original sealed containers, in cool and ventilated area.
Store in a well-ventilated area. Keep away from any source of heat, dampness, humidity, oxidising agents or direct sunlight. Flammable before curing. Keep away from sources of ignition.

HEALTH AND SAFETY:
For more information, please refer to the relevant safety data sheet.

Quality, Environment and Safety Management
SOPREMA always recognises as a high level of importance, the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with EN ISO 9001 and EN ISO 14001.

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations without notice.

ELASTOCOL STICK

Primer designed to enhance the adhesion of Soprema self-adhesive membranes

September 2026

STATEMENT OF RESPONSIBILITIY:
The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of general nature, no assumption can be made as to a products suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other that those required the suitability of products for their intended use.

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No

MANUFACTURERS CONTACT DETAILS:

Manufacture location	Canada
Legal and trading name of manufacturer	Soprema New Zealand Limited
Manufacturer address for service	Level 3, Candida Building 4, 61 Constellation Drive, Mairangi Bay, Auckland 0630, New Zealand
Manufacturer website	www.soprema.com.au
Manufacturer email	info@soprema.com.au
Manufacturer phone number	+61 3 9221 6230
Manufacturer NZBN	9429050312962

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations without notice.