

# ELASTOCOL STICK

Primer designed to enhance the adhesion of Soprema self-adhesive membranes

April 2026

## DESCRIPTION:

ELASTOCOL STICK is a primer designed to enhance the adhesion of Soprema self-adhesive membranes on porous surfaces such as "DENS GLASS GOLD" and "DENS DECK" at temperatures above -10°C.

ELASTOCOL STICK is composed of SBS synthetic rubbers, adhesive enhancing resins and volatile solvents. It is also suitable to prime non-porous surfaces such as concrete, fibre cement, metal and wood.

## METHOD OF APPLICATION:

ELASTOCOL STICK can be applied with a brush, a roll or a spray can. Shake well before using. It must be thoroughly dry before applying the waterproofing membrane. Drying time will vary depending on air and surface temperature and humidity.

**WARNING:** Do not accelerate drying of ELASTOCOL STICK by heating with a torch.

## PACKAGING:



| Specifications  | Elastocol Stick                                   |
|-----------------|---|
| Physical State  | Liquid  |
| Colour          | Red   |
| Coverage        | Porous surfaces: 0.3 to 0.5 l/m <sup>2</sup>      |
|                 | Non-porous surfaces: 0.1 to 0.25 l/m <sup>2</sup> |
| Packaging       | 19L   |
| Pail per pallet | 36  |

## PROPERTIES:

| Properties                | Elastocol Stick   |
|---------------------------|---|
| Specific gravity at 20°C  | 0.79 kg/l   |
| Solids by weight          | 24%   |
| Brookfield Viscosity 25°C | 200 cP  |
| Packaging                 | 19L   |
| Drying time               | 15 to 60 minutes, depending on temperature and quantity applied |

## STORAGE AND HANDLING:

Shelf life: Up to 60 months in original sealed containers, in cool and ventilated area.

Store in a well-ventilated area. Keep away from any source of heat, dampness, humidity, oxidising agents or direct sunlight.

Flammable before curing. Keep away from sources of ignition.

## HEALTH AND SAFETY:

For more information, please refer to the relevant safety data sheet.

## Quality, Environment and Safety Management

SOPREMA always recognises as a high level of importance, the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with EN ISO 9001 and EN ISO 14001



# ELASTOCOL STICK

Primer designed to enhance the adhesion of Soprema self-adhesive membranes

April 2026

## STATEMENT OF RESPONSIBILITY:

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of general nature, no assumption can be made as to a products suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required the suitability of products for their intended use.

## WARNINGS AND BANS:

|  |    |
|--|----|
| Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004? | No |
|--|----|

## MANUFACTURERS CONTACT DETAILS:

|  |   |
|--|---|
| Manufacture location                   | Belgium   |
| Legal and trading name of manufacturer | Soprema New Zealand Limited   |
| Manufacturer address for service       | Level 3, Candida Building 4, 61 Constellation Drive, Mairangi Bay, Auckland 0630, New Zealand |
| Manufacturer website                   | <a href="http://www.soprema.com.au">www.soprema.com.au</a>                                    |
| Manufacturer email                     | <a href="mailto:info@soprema.com.au">info@soprema.com.au</a>                                  |
| Manufacturer phone number              | +61 3 9221 6230   |
| Manufacturer NZBN                      | 9429050312962   |

