

SOPRADERE QUICK

Cold applied fast drying primer

January 2025



PURPOSE AND AREAS OF USE:

Cold applied fast drying primer based on bitumen, solvents and adhesion-improving additives. Impregnation to ensure good adhesion to substrate (concrete, metal and wood) before welding (torch-on or hot-air method) or gluing bituminous waterproofing membranes. It is also suitable on old/weathered bituminous waterproofing membranes with a slate or granulated finish.

STANDARD PACK:

Can of 5 and 25 L.

PROPERTIES:

Composition	Bitumen, solvents and adhesion-improving additives.
Curing time	530 min.
Consumption (l/m ²)	0.15-0.25
Application temperature	Min +5°C
Coverage rate	5-6 sqm ² /L

INSTALLATION:

Thoroughly mix the product before use. Apply with a brush, roller or rubber squeegee on a dry, dust and grease free substrate. Allow to dry completely before applying the membrane. See label for more information.

CLEANING:

Wet product - white spirit.

HEALTH AND SAFETY:

For more information, please refer to the relevant Safety Data Sheet (SDS).

SOPREMA has always attached the highest importance to the quality of the products, the environment and safety. For this reason, they operate independently monitored Quality and Environment Assurance Systems in line with EN ISO 9001 and EN ISO 14001.

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
--	----

MANUFACTURERS CONTACT DETAILS:

Manufacture location	Belgium
Legal and trading name of manufacturer	Soprema New Zealand Limited
Manufacturer address for service	Level 3, Candida Building 4, 61 Constellation Drive, Mairangi Bay, Auckland 0630, New Zealand
Manufacturer website	www.soprema.com.au
Manufacturer email	info@soprema.com.au
Manufacturer phone number	+61 3 9221 6230
Manufacturer NZBN	9429050312962