

AQUAFIN®-CJ6

Thermoplastic expansive waterstop for waterproofing construction joints

July 2026

PROPERTIES:

- Simple application
- Rapid and strong expansion
- Self-injecting function into cracks and voids
- Completely dimensionally stable even at high temperatures
- Swelling process inexhaustible, often reversible
- Suitable for fresh water and seawater applications
- Tested to 4 bar water pressure

AREAS OF APPLICATION:

- Aquafin-CJ6 is used for waterproofing the inner side of concrete construction joints in accordance with Building Regulations list A, part 2, serial number .53, where there is constant or intermittent exposure to ground water, run-off water and/or surface water.
- Aquafin-CJ6 is suitable for riparian zones. Construction joints can be sealed watertight to a depth of 8 m.
- Aquafin-CJ6 is suitable for application class A, exposure levels 1 and 2 in accordance with the waterproofing guidelines of the German reinforced concrete commission (*1)

TECHNICAL DATA:

	Aquafin-CJ6
Basis	TPE (thermoplastic elastomer)
Format	Waterstop profile is quadratic and flexible
Colour	Red
Density	Approx. 1.25 g/m³
Sealing against water pressure until (in accordance with BBA)	4 bar
Shore A hardness (DIN 53505)	Approx. 6 hours
Swelling capacity (demineralised water)	Approx. 50% after 2 hours Approx. 460% after 24 hours >700% after 8 days
Expansive pressure	Approx. 1.06 N/mm²
Water impermeability after installation - Joint width 0.25 mm - Joint width 1.0 mm	2 bar 1.5 bar
Toxicity	None
Reaction to fire	Class E to DIN EN 13501-1
Application temperature	0-50 °C
Packaging	40m Roll, 5 x 40m Box
Storage	2 years when stored dry, frost free and protected against weathering in unopened original container

SUBSTRATE PREPARATION:

The substrate must be load-bearing, mostly flat and have a closed surface texture. It must be free from gravel pockets, cavities, gaping cracks, dust and free from adhesion inhibiting substances. Laitance layers are to be removed, mechanically abraded (sand blasted) as necessary. During the application of Aquafin-CJ6 the substrate may be matt damp. The formation of puddles is not permitted.

AQUAFIN®-CJ6

Thermoplastic expansive waterstop for waterproofing construction joints

July 2026

APPLICATION:

It is essential that there is at least >8 cm coverage of concrete from the side exposed to water. Bond Aquafin-CJ6 with a mounting adhesive suitable for waterstops. Completely cover the prepared substrate with the mounting adhesive and press the Aquafin-CJ6 into the adhesive until it oozes out from beneath. Do not begin the concrete process for at least 8 hours after bonding.

Alternatively, Aquafin-CJ6 can also be fastened with steel nails (min. 5 nails/m). When doing so, it is necessary to ensure substrate contact pressure covering the whole area.

Avoid looping or hollow layers. Waterstop connections can be made by overlapping by 5 cm or by butt jointing. The waterstops must be placed tightly together to prevent gaps. Butt jointed waterstops must be covered by a separate section of waterstop with a 3 cm overlap to both sections.

ADVICE:

- It is essential to store the waterstop dry.
- Waterstops must lie flat and planar on the concrete. There must be no contaminants beneath the waterstop.
- Protect the waterstop from moisture until the concrete is poured.
- Before commencing the concreting process visually inspect the waterstop. Heavily swollen waterstop tape is unsuitable and must be removed.
- Waterstops are not suitable for movement joints.
- Follow current relevant regulations and data sheets. Therefore e.g.
 - Guidelines "Water impermeable concrete structures".
 - German reinforced concrete commission (DafStb)
 - Data sheet "Injection grouting hose systems and expansive inlays for construction joints", German Concrete and Construction Technology Association.

HEALTH AND SAFETY:

Health and Safety information can be found on the Safety Data Sheet (SDS).

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
--	----

MANUFACTURERS CONTACT DETAILS:

Manufacture location	Germany
Legal and trading name of manufacturer	SCHOMBURG GmbH & Co. KG
Manufacturer address for service	Aquafinstr. 2-8 D-32760 Detmold (Germany)
Manufacturer website	Schomburg.com
Manufacturer email	
Manufacturer phone number	+49 5231 953 00
Manufacturer NZBN	