

EQUUS TRAXX FLOORING SYSTEM

Hard wearing, chemical resistant, polyurethane floor coating

July 2026

PURPOSE AND AREAS OF USE:

The system is a single-component chemical and abrasion resistant polyurethane floor coating, with a substrate appropriate primer. It provides an easy to clean, hygienic, heavy duty yet economical floor finish. Available in a smooth finish or a medium or coarse non-skid grade depending on the end use requirements of the floor.

PRODUCT:

The system encompasses the products below. Refer to standard Equus Traxx specifications for full specification details.

Traxx Primer 1050	Traxx Primer 1070
Chevaline Epistixx	Protexx Zincure
Traxx	Traxx NS
Range of Traxx topcoats where required	

COLOUR:

Equus Traxx is available in a range of oxide colours including brown, red, yellow and terracotta, and in concrete grey. Selected mid-tone colours from BS2660 and BS4800 can be produced, subject to minimum order quantities and possible surcharge. Can be colour matched to any colour palate.

SCOPE OF USE:

Equus Traxx is suitable for a range of substrates (with the correct primer), including concrete, plaster, tile, timber, and steel. Generally, it is used over new or existing concrete flooring in a variety of commercial areas as a heavy duty, chemical resistant interior finish. Suitable for use in Clean Rooms as it holds the ISO 14644 Clean Room standard approval.

Traxx can be used in areas subjected to traffic or where non-slip characteristics are essential, and/or where protection of the substrate from aggressive agents is required. Traxx smooth and non-skid can be applied to vertical surfaces.

CONDITIONS OF USE:

Equus Traxx Flooring System must be used in accordance with the correct specifications and substrates mentioned in this TDS, or in other Equus approved technical documentation.

Not suitable as a heavy-duty floor finish. Not suitable for exterior conditions or in areas of with UV exposure except where specifically approved by Equus Industries.

BUILDING CODE COMPLIANCE:

When used with the correct specification the product complies with the following building code clauses:

B2 Durability - B2.3.1(c) Equus Traxx Flooring System has a durability of at least 5 years when installed with the correct specification, installation and maintenance.

D1 Access Routes - D1.3.3(d) Equus Traxx Flooring System complies with D1/AS1 on level surfaces, and on sloping surfaces and stairs with the use of Equus Traxx NS (non-skid)

F2 Hazardous building materials - F2.3.1 Equus Traxx Flooring System is a waterborne material and contains no mammalian-toxic substances. Refer to product SDS's at www.equus.nz

SUPPORTING DOCUMENTATION:

Can be found at: www.equus.nz

EQUUS TRAXX FLOORING SYSTEM

Hard wearing, chemical resistant, polyurethane floor coating

July 2026

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
--	----

MANUFACTURERS CONTACT DETAILS:

Manufacture location	New Zealand
Legal and trading name of manufacturer	Equus Industries Ltd.
Manufacturer address for service	4 Sheffield Street, Blenheim 7274
Manufacturer website	www.equus.nz
Manufacturer email	info@equus.nz
Manufacturer phone number	03 578 0214
Manufacturer NZBN	9429032000306